

Medida estándar		Peso teórico			
Pulg.	mm.	Kg/m	Kg/pza.		
1/8"	3/4"	19.1	.88	5.368	
	1"	3.18	25.4	1.19	7.259
	1 1/4"		31.8	1.50	9.15
	1 1/2"		38.1	1.83	11.163
	1 3/4"		44.5	2.14	13.054
	2"		50.8	2.46	15.006
3/16"	1"		25.4	1.73	10.553
	1 1/4"	4.76	31.8	2.20	13.42
	1 1/2"		38.1	2.68	16.348
	1 3/4"		44.5	3.15	19.215
	2"		50.8	3.63	22.143
	2 1/2"		63.5	4.61	28.121
	3"		76.2	5.52	33.672
3 1/2"		88.9	6.55	39.955	
1/4"	1"		25.4	2.22	13.542
	1 1/4"	6.35	31.8	2.86	17.446
	1 1/2"		38.1	3.48	21.228
	1 3/4"		44.5	4.12	25.132
	2"		50.8	4.75	28.975
	2 1/2"		63.5	6.10	37.21
	3"		76.2	7.29	44.469
	3 1/2"		88.9	8.63	52.643
	4"		101.6	9.82	59.902
5/16"	2"		50.8	5.83	35.563
	2 1/2"		63.5	7.44	45.384
	3"	7.94	76.2	9.08	55.388
	3 1/2"		88.9	10.71	65.331
	4"		101.6	12.20	74.42
	5"		127.0	15.47	94.367
3/8"	2"		50.8	6.99	42.639
	2 1/2"		63.5	8.78	53.558
	3"	9.52	76.2	10.72	65.392
	3 1/2"		88.9	12.65	77.165
	4"		101.6	14.58	88.938
	5"		127.0	18.30	111.63
	6"		152.4	22.17	135.237
1/2"	3"		76.2	13.99	85.339
	3 1/2"		88.9	16.52	100.772
	4"	12.70	101.6	19.05	116.205
	5"		127.0	24.11	147.071
	6"		152.4	29.17	177.937
5/8"	4"		101.6	23.36	142.496
	6"	15.88	152.4	36.01	219.661
3/4"	6"	19.05	152.4	42.71	260.531

ÁNGULO

Figura de lámina de acero en forma de " L " con lados comúnmente iguales, se utiliza de acuerdo a sus propiedades y características

USOS

- Armado de viga joist
- Componentes de maquinaria
- Refuerzos de estructura

