

# TUBERÍA DE CONDUCCIÓN / ESTRUCTURAL



Diámetro Nominal	Diámetro Exterior (D)		Espesor (T)		Identificación stadar (STD), Extra fuerte (XS), o doble extra fuerte (XXS)	CED. No.	Peso	
	Pulg.	mm.	Pulg.	mm.			Lb./ft	Kg./m
6	6.625	168.3	0.188	4.78	STD	40	12.94	19.251
			0.280	7.11			18.99	28.261
			0.312	7.92			21.05	31.332
8	8.625	219.1	0.188	4.78	STD	20	16.96	25.232
			0.250	6.35			22.38	33.307
			0.312	7.92			27.72	41.259
			0.322	8.18			28.58	42.530
			0.375	9.53			33.07	49.214
10	10.750	273.1	0.188	4.78	STD	20	21.23	31.587
			0.250	6.35			28.06	41.757
			0.312	7.92			34.81	51.806
			0.365	9.27			40.52	60.298
			0.375	9.35			41.59	61.891
12	12.750	323.9	0.250	6.35	STD	40	21.23	31.587
			0.250	6.35			28.06	41.757
			0.312	7.92			34.81	51.806
			0.365	9.27			40.52	60.298
			0.375	9.35			41.59	61.891
14	14.000	355.6	0.250	6.35	XS	60	54.78	81.526
			0.312	7.92			41.48	61.732
			0.375	9.53			49.61	73.821
			0.406	10.31			53.57	79.724
			0.500	12.70			65.47	97.434
16	16.000	406.4	0.250	6.35	STD	10	36.74	54.682
			0.312	7.92			45.65	67.936
			0.375	9.53			54.62	81.278
			0.500	12.70			72.15	107.375
			0.625	15.88			89.36	132.978
18	18.000	457.2	0.250	6.35	XS	20	42.09	62.636
			0.312	7.92			52.32	77.862
			0.375	9.53			62.63	93.209
			0.500	12.70			82.84	123.284
			0.625	15.88			102.72	152.862
20	20.000	508.0	0.250	6.35	STD	10	47.43	70.590
			0.312	7.92			58.99	87.789
			0.375	9.53			70.65	105.139
			0.500	12.70			93.53	139.192
			0.625	15.88			116.76	172.747
20	20.000	508.0	0.250	6.35	XS	30	52.78	78.544
			0.312	7.92			65.66	97.715
			0.375	9.53			78.67	117.070
			0.500	12.70			104.22	155.099
			0.625	15.88			129.44	192.631