

Medida estándar		Peso teórico			
Pulg.	mm.		Kg/m	Kg/pza.	
1/8"	1/2"		12.7	0.317	1.93
	3/4"	3.175	19.1	0.476	2.90
	1"		25.4	0.633	3.86
	1 1/4"		31.7	0.790	4.82
	1 1/2"		38.1	0.950	5.79
	2"		50.8	1.266	7.72
	2 1/2"		63.5	1.583	9.65
	3"		76.2	1.899	11.59
3/16"	1/2"		12.7	0.476	2.90
	3/4"	4.775	19.1	0.716	4.37
	1"		25.4	0.952	5.81
	1 1/4"		31.7	1.188	7.25
	1 1/2"		38.1	1.428	8.71
	2"		50.8	1.904	11.61
	2 1/2"		63.5	2.380	14.52
	3"		76.2	2.856	17.42
1/4"	1/2"		12.7	0.633	3.86
	3/4"	6.350	19.1	0.952	5.81
	1"		25.4	1.266	7.72
	1 1/4"		31.7	1.580	9.64
	1 1/2"		38.1	1.899	11.58
	2"		50.8	2.532	15.45
	2 1/2"		63.5	3.165	19.31
	3"		76.2	3.798	23.17
	4"		101.6	5.065	30.90
	5"		127.0	6.331	38.62
6"		152.4	7.597	46.34	
3/8"	1 1/2"		38.1	2.849	17.38
	2"	9.525	50.8	3.798	23.17
	2 1/2"		63.5	4.748	28.96
	3"		76.2	5.698	34.76
	4"		101.6	7.597	46.34
	5"		127.0	9.496	57.93
	6"		152.4	11.395	69.51
1/2"	1 1/2"		38.1	3.798	23.17
	2"	12.700	50.8	5.065	30.90
	2 1/2"		63.5	6.331	38.62
	3"		76.2	7.597	46.34
	4"		101.6	10.129	61.79
	5"		127.0	12.661	77.23
	6"		152.4	15.194	92.68
	8"		203.2	20.258	123.57
	10"		254.0	25.322	154.46
	12"		304.8	30.388	185.37
5/8"	1 1/2"		38.1	4.748	28.96
	2"	15.875	50.8	6.331	38.62
	2 1/2"		63.5	7.913	48.27
	3"		76.2	9.496	57.93
	4"		101.6	12.661	77.23
	5"		127.0	15.827	96.54
	6"		152.4	18.992	115.85
	8"		203.2	25.322	154.46
	10"		254.0	31.654	193.09
	12"		304.8	37.984	231.70

SOLERA

Barra rectangular de acero, se maneja en 2 diferentes tipos, uno es solera de placa que proviene de rollo y la otra solera de fundición que proviene de molino fundidor, cada una con diferentes especificaciones adaptable para diferentes tipos de proyectos.

